



### KEY FEATURES



ADHERES TO MOST SURFACES



EASY REMOVAL



HIGH TEMPERATURES



WATER RESIST



NO RESIDUE

### TYPICAL APPLICATIONS

Masking tape suitable for 80°C 1 hour oven baking. Suitable for miscellaneous industrial, automotive, construction and other painting applications.

### ADVANTAGES AND BENEFITS

- Premium water resist paper
- Excellent adhesion to most surfaces
- Easy application on curved profiles and irregular surfaces
- Easy removal
- No residue
- Compatible with solvent based paints and most water based paints
- 80°C 1 hour temperature service

### CONSTRUCTION

- Backing: Saturated water resist crepe paper
- Adhesive: Natural rubber & hydrocarbon resins
- Available Color: Green

| Green      |                     |
|------------|---------------------|
| 24mm x 45m | 36 Rolls per carton |
| 48mm x 45m | 20 Rolls per carton |

### TECHNICAL DATA

| Masking Tape           | METRIC      |
|------------------------|-------------|
| Paper grammage         | 70 Gsm      |
| Total thickness        | 145 Micron  |
| Peel adhesion          | 2,7 N/cm    |
| Tensile strength       | 42 N/cm     |
| Elongation at break    | 10%         |
| Temperature resistance | 80°C 1 hour |

Physical and performance characteristics shown above are obtained following tests recommended by AFERA. The values given are typical values and do not constitute a specification. The user should determine whether the tape is suitable for the intended application.



### STORAGE

Tape performance is guaranteed within the first 6 months. Product must be kept in its original box and in a dry atmosphere away from direct sunlight. For product traceability, please advise the 12 digit batch number printed on labels.

### SECURITY

Product does not contain any dangerous or unhealthy components. Security data sheets are available based on directive 91/155/EC. All our tapes comply with European 2004/12/CE Packaging directive.